



Dual Column H160XLA-DC-C

Capacity: 25" High x 36" Wide

Blade Size: 2" x 24'0" x .063"

Motor: 15 HP

Hydraulics: 5 HP

DESIGNED AND BUILT IN THE



Standard Features:

- Swing-Away Console - All Function Control
- Solid State Programmable Logic Controller
- Full Stroking Vises
- Guide Cap Camlocks
- Push Button Blade Speed w/ LED Readout
- Blade Chip Brush
- Powered Moveable Guide Arm
- Arm Height Adjustment From the Console
- Chip Auger System
- Automatic Shut Off
- Powered Blade Tension
- Cut Watcher System
- Electronically Controlled Traverse (ECT)
Controls Feed Rate & Cutting Force
- Computer Controlled Feed System (CCF)
- Material Jogging Feature
- Flood Coolant System
- 24" Roller Discharge Table
- 3rd Vise on Feed
- 0 - 24" Stroke Bar-Feed

Optional Features:

- Set of Full Capacity Top Clamps - Main & Feed
- Full Capacity Top Clamp - Main Vise
- Full Capacity Top Clamp - Outboard Vise
- Blade Enhancer System
- Laser Light System
- Shadow Light System
- Outboard Powered Vise on Dishcharge
- 0 - 72" Stroke Bar Feed System w/ 3rd Vise
- Hydraulic Computer Controlled Traverse (HCCT)
- Solid Base in Lieu of Rollers
- Spray Mist Coolant System
- Pedestal Mounted Console

P. O. Box 1148 • Pryor, OK • 74362

www.hemsaw.com

Toll Free: (888) 729-7787 • Phone: (918) 825-4821
Fax: (918) 825-4824 • E-Mail: info@hemsaw.com