

HEM & SAW

—The saw that cuts straight.—

Vertical Series VT100LA-60

Capacity: 18" Horizontal x 20.75" Vertical @ 90°
18" Horizontal x 14.25" Vertical @ 45° (Left)
18" Horizontal x 14" Vertical @ 45° (Right)
18" Horizontal x 9.75" Vertical @ 60° (Left)
18" Horizontal x 6.75" Vertical @ 60° (Right)

Blade Size: 1-1/4" x 15'6" x .042"

Motor: 5 HP

Arm Cant: 3° - Non-Adjustable

DESIGNED AND BUILT IN THE

U.S.A. 



Console Pivots from Front
to Right Side of Saw

Standard Features:

Swing Away Console
- All Function Control
- Touch Cut Screen
Powered Main & Feed Vise
Variable Vise Pressure
Powered Blade Tension
Powered Guide Arm
Powered Arm Tilt
Infinitely Variable Blade Speed Drive
- 70-300 SFPM
LED Blade Speed Readout
Adjustable Cutting Pressure & Feed Rate
Cut Watcher System
Forward Cut Stop
Flood Coolant System
0-24" Stroke Bar Feed System (4 Indexes)
Set of Idle, Non-Lifting Rollers
- One on Each Side of Saw Base
Boltable Side Wings



**Shown w/ Optional 2nd Main Vise*

Optional Features:

- Second Main Machine Vise
- 3rd Holding Vise on Feed
- Full Capacity Swing-Away Top Clamp
- Main Vise
- Full Capacity Top Clamp - Feed Vise
- Laser Light System
- Spray Mist Coolant System
- Feed Direction Change to Right Side
- Idle & Powered Tables

www.hemsaw.com

P. O. Box 1148 • Pryor, OK • 74362

Toll Free: (888) 729-7787 • Phone: (918) 825-4821

Fax: (918) 825-4824 • E-Mail: info@hemsaw.com

Hem, Inc., whose policy is one of continuous improvement, reserves the right to change the price, specifications, or design, as well as discontinue any model, at any time without notice and without incurring any obligations. Dimensions may vary. Please contact Hem, Inc. for a certified dimensional drawing of your specific model. Copyright 112800 Hem, Inc. All rights reserved.