

HEM[&]SAW

— The saw that cuts straight. —

Vertical Series VT100LM-60

Capacity: 18" Horizontal x 20.75" Vertical @ 90° (22.5 w/o Cant)
18" Horizontal x 14.25" Vertical @ 45° (Left) (15.25 w/o Cant)
18" Horizontal x 14" Vertical @ 45° (Right) (15.125 w/o Cant)
18" Horizontal x 9.75" Vertical @ 60° (Left) (10.25 w/o Cant)
18" Horizontal x 6.75" Vertical @ 60° (Right) (7.25 w/o Cant)

Blade Size: 1-1/4" x 15'6" x .042"

Arm Cant: 3° - Arm Can Be Adjusted to Straight Cut Position

Motor: 5 HP



Console Pivots from Front to Right Side of Saw

Standard Features:

- Swing-Away Console on Front of Saw
- Protractor Scale for Miter Angle
- Powered Blade Cleaning Brush
- Powered Main Machine Vise
- Variable Vise Pressure
- Carbide Blade Guides
- Forward Cut Stop
- Powered Guide Arm
- Adjustable Cutting Pressure
- Adjustable Feed Rate
- Built-In Coolant System

Optional Features:

- Second Main Machine Vise
- Non-Mitered Vise Wear Plates
- Spray Mist Coolant System
- Swing-Away Top Clamp - Main Vise
- Powered Blade Tension
- Laser Light
- Powered Head Tilt
- Solid Discharge Table
- Idle & Powered Tables

www.hemsaw.com

P. O. Box 1148 • Pryor, OK • 74362

Toll Free: (888) 729-7787 • Phone: (918) 825-4821

Fax: (918) 825-4824 • E-Mail: info@hemsaw.com

Hem, Inc., whose policy is one of continuous improvement, reserves the right to change the price, specifications, or design, as well as discontinue any model, at any time without notice and without incurring any obligations. Dimensions may vary. Please contact Hem, Inc. for a certified dimensional drawing of your specific model. Copyright 112800 Hem, Inc. All rights reserved.