

HEM[&]SAW

— The saw that cuts straight. —

Vertical Series VT120HA-60

Capacity: 18" Horizontal x 24" Vertical @ 90°
18" Horizontal x 16" Vertical @ 45° (Left)
18" Horizontal x 14.75" Vertical @ 45° (Right)
18" Horizontal x 9" Vertical @ 60° (Right)

Blade Size: 1-1/4" x 16'6" x .042"

Motor: 7.5 HP

Hydraulics: 5 HP

Arm Cant: 3°

DESIGNED AND BUILT IN THE

U.S.A. 



**Shown w/ Optional Top Clamps,
2nd Main Vise, and 3rd Holding Vise*

Standard Features:

Swing Away Console

- All Function Control

Full Stroking Vises

Powered Blade Tension

Powered Guide Arm

Programmable Tilt

Powered Tilt with Angle Read Out

LED Blade Speed Read-Out

Electronically Controlled Traverse (ECT)

Controls Feed Rate & Cutting Force

Cut Watcher System

Computer Controlled Feed System

Flood Coolant System

0-48" Stroke Bar Feed System

Powered Lift-Up Feed Table

Material Jogging Feature

Optional Features:

• Second Main Machine Vise

• 3rd Holding Vise

• Blade Saver System

• Full Capacity Top Clamps - Main & Feed Vises

• Reduced Capacity Top Clamps

- Main & Feed Vises

• Laser Light System

• Powered Chip Conveyor System

• 0-72" Stroke Bar Feed System

- w/ 3rd Holding Vise

• Spray Mist Coolant System

• Feed Direction Change to Right Side

• Powered Raised Lift-Up Rollers

• Idle & Powered Tables

www.hemsaw.com

P. O. Box 1148 • Pryor, OK • 74362

Toll Free: (888) 729-7787 • Phone: (918) 825-4821

Fax: (918) 825-4824 • E-Mail: info@hemsaw.com

Hem, Inc., whose policy is one of continuous improvement, reserves the right to change the price, specifications, or design, as well as discontinue any model, at any time without notice and without incurring any obligations. Dimensions may vary. Please contact Hem, Inc. for a certified dimensional drawing of your specific model. Copyright 112800 Hem, Inc. All rights reserved.