

HEM[®] & SAW

—The saw that cuts straight.—

Vertical Series VT120HA-60

Capacity: 18" Horizontal x 24" Vertical @ 90°
18" Horizontal x 16" Vertical @ 45° (Left)
18" Horizontal x 14.75" Vertical @ 45° (Right)
18" Horizontal x 10" Vertical @ 60° (Left)
18" Horizontal x 9" Vertical @ 60° (Right)

DESIGNED AND BUILT IN THE

U.S.A. 

Blade Size: 1-1/4" x 16'6" x .042"

Motor: 7.5 HP

Hydraulics: 5 HP

Arm Cant: 3°



**Shown w/ Optional Top Clamps,
2nd Main Vise, and 3rd Holding Vise*

Standard Features:

Swing Away Console
- All Function Control
Full Stroking Vises
Powered Blade Tension
Powered Guide Arm
Programmable Tilt
Powered Tilt with Angle Read Out
Infinitely Variable Blade Speed Drive
LED Blade Speed Read-Out
Electronically Controlled Traverse (ECT)
Controls Feed Rate & Cutting Force
Cut Watcher System
Computer Controlled Feed System
Flood Coolant System
0-48" Stroke Bar Feed System
Powered Lift-Up Feed Table
Material Jogging Feature

Optional Features:

- Second Main Machine Vise
- 3rd Holding Vise
- Blade Saver System
- Full Capacity Top Clamps - Main & Feed Vises
- Reduced Capacity Top Clamps
- Main & Feed Vises
- Laser Light System
- Powered Chip Conveyor System
- 0-72" Stroke Bar Feed System
- w/ 3rd Holding Vise
- Spray Mist Coolant System
- Feed Direction Change to Right Side
- Powered Raised Lift-Up Rollers
- Idle & Powered Tables

www.hemsaw.com

P. O. Box 1148 • Pryor, OK • 74362

Toll Free: (888) 729-7787 • Phone: (918) 825-4821

Fax: (918) 825-4824 • E-Mail: info@hemsaw.com

Hem, Inc., whose policy is one of continuous improvement, reserves the right to change the price, specifications, or design, as well as discontinue any model, at any time without notice and without incurring any obligations. Dimensions may vary. Please contact Hem, Inc. for a certified dimensional drawing of your specific model. Copyright 112800 Hem, Inc. All rights reserved.