

HEM & M[®] SAW

—The saw that cuts straight.—

Vertical Series VT120HM-60

Capacity: 18" Horizontal x 24" Vertical @ 90°
18" Horizontal x 16" Vertical @ 45° (Left)
18" Horizontal x 14.75" Vertical @ 45° (Right)
18" Horizontal x 10" Vertical @ 60° (Left)
18" Horizontal x 9" Vertical @ 60° (Right)

Blade Size: 1-1/4" x 16'6" x .042"

Motor: 7.5 HP

Hydraulics: 5 HP

Arm Cant: 3°

DESIGNED AND BUILT IN THE

U.S.A. 



Standard Features:

- Swing-Away Console
- Power Tilt w/ LED Angle Readout
- Full Stroking Main Vise
- Variable Vise Pressure
- Infinitely Variable Blade Speed Drive
- LED Blade Speed Readout
- Carbide Blade Guides
- Forward Cut Stop
- Powered Guide Arm
- Electronically Controlled Traverse (ECT)
 - Controls Feed Rate & Cutting Force
- Powered Blade Tension
- Built-In Coolant System

Optional Features:

- Second Main Machine Vise
- Spray Mist Coolant System
- Swing-Away Full Capacity Top Clamp - Main Vise
- Reduced Capacity Top Clamp - Main Vise
- Cut Watcher System
- Laser Light
- Manual Hand Crank Chip Conveyor
- Powered Chip Conveyor
- Power Raised Lift-Up Rollers
- Idle & Powered Load Tables
- Idle & Powered Discharge Tables

www.hemsaw.com

P. O. Box 1148 • Pryor, OK • 74362

Toll Free: (888) 729-7787 • Phone: (918) 825-4821

Fax: (918) 825-4824 • E-Mail: info@hemsaw.com

Hem, Inc., whose policy is one of continuous improvement, reserves the right to change the price, specifications, or design, as well as discontinue any model, at any time without notice and without incurring any obligations. Dimensions may vary. Please contact Hem, Inc. for a certified dimensional drawing of your specific model. Copyright 112800 Hem, Inc. All rights reserved.