



Vertical Series VT200A-60 SS

Capacity: 25" Horizontal x 36" Vertical @ 90°
25" Horizontal x 25" Vertical @ 45°
25" Horizontal x 17" Vertical @ 60°

Blade Size: 2" x 24'8" x .063"

Motor: 15 HP

Hydraulics: 5 HP

Arm Cant: 4°

DESIGNED AND BUILT IN THE

U.S.A. 



Standard Features:

- Free Standing Console
 - All Function Control
- Icon Driven Menu
- Full Stroking Vises
- Powered Guide Arm
- Powered Tilt with Angle Read Out
- Programmable Tilt
- Variable Frequency Drive for Blade Speed
- LED Blade Speed Read-Out
- Electronically Controlled Traverse (ECT)
 - Controls Feed Rate & Cutting Force
- 0-72" Stroke Bar Feed System - Smart Feed
 - w/ Rollers All the Way Through
- Powered Lift-Up Feed Table
- 3rd Holding Vise on Feed
- Power Raised Lift-Up Rollers
 - One on Each Side of Saw Base
- Computer Controlled Feed System
- Material Jogging Feature
- Powered Blade Tension

Additional Standard Features:

- Swing Away Full Capacity Top Clamp
 - Main Vise
- Full Capacity Top Clamp - Feed Vise
- Cut Watcher System
- Powered Chip Conveyor
- Blade Saver System
- Flood Coolant System

Optional Features:

- Spray Mist Coolant System
- Laser Light System
- Feed Direction Change to Right Side
- Idle & Powered Tables

www.hemsaw.com

P. O. Box 1148 • Pryor, OK • 74362

Toll Free: (888) 729-7787 • Phone: (918) 825-4821

Fax: (918) 825-4824 • E-Mail: info@hemsaw.com

Hem, Inc., whose policy is one of continuous improvement, reserves the right to change the price, specifications, or design, as well as discontinue any model, at any time without notice and without incurring any obligations. Dimensions may vary. Please contact Hem, Inc. for a certified dimensional drawing of your specific model. Copyright 112800 Hem, Inc. All rights reserved.