

HEM[&]SAW

—The saw that cuts straight.—

Vertical Series VT200A-60

Capacity: 25" Horizontal x 36" Vertical @ 90°
25" Horizontal x 25" Vertical @ 45°
25" Horizontal x 17" Vertical @ 60°

Blade Size: 2" x 24'8" x .063"

Motor: 15 HP

Hydraulics: 5 HP

Arm Cant: 4°



**Shown w/ Optional Top Clamps*

Standard Features:

Swing Away Console

- All Function Control

Solid State Programmable Logic Controller

Full Stroking Vises

Powered Guide Arm

Powered Tilt with Angle Read Out

Variable Frequency Drive for Blade Speed

LED Blade Speed Read-Out

Electronically Controlled Traverse (ECT)

Controls Feed Rate & Cutting Force

Cut Watcher System

0-72" Stroke Bar Feed System

Powered Lift-Up Feed Table

3rd Holding Vise on Feed

Power Raised Lift-Up Rollers

- One on Each Side of Saw Base

Computer Controlled Feed System

Material Jogging Feature

Powered Chip Conveyor

Powered Blade Tension

Flood Coolant System



DESIGNED AND BUILT IN THE

U.S.A. 

Optional Features:

- Blade Saver System
- Swing Away Full Capacity Top Clamp - Main Vise
- Laser Light System
- Full Capacity Top Clamp - Feed Vise
- Spray Mist Coolant System
- Feed Direction Change to Right Side
- Idle & Powered Tables

www.hemsaw.com

P. O. Box 1148 • Pryor, OK • 74362

Toll Free: (888) 729-7787 • Phone: (918) 825-4821

Fax: (918) 825-4824 • E-Mail: info@hemsaw.com

Hem, Inc., whose policy is one of continuous improvement, reserves the right to change the price, specifications, or design, as well as discontinue any model, at any time without notice and without incurring any obligations. Dimensions may vary. Please contact Hem, Inc. for a certified dimensional drawing of your specific model. Copyright 112800 Hem, Inc. All rights reserved.