



Wide Flange WF190MRB-DC

Capacity: 25" H x 44" W @ 90°
25" H x 27" W @ 45° Both Directions
Blade Size: 2" x 30'6" x .063"
Arm Tilt: 7°
Motor: 15 HP
Hydraulics: 5 HP



Rotary Bearing Base



Standard Features:

- Free Standing Control Console w/ 25' Umbilical
- Powered Blade Tension
- Powered Moveable Guide Arm
- Power Miter w/ Angle Readout
- LED Blade Speed Readout on Console
- Variable Frequency Controller for Blade Speed
- Vising on Both Sides of Blade
- Flood Coolant System
- Roller Base Machine
- Blade Chip Brush
- Blade Stall Switch
- Flat Carbide Blade Guides
- Guide Cap Camlocks
- Hydraulic Computer Controlled Traverse (HCCT)
- Adjustable Clamping Pressure (0-2, 500 lbs)
- Adjustable Feed Rate & Cutting Pressure
- Blade Guards for Safety



Optional Features:

- Chip Auger System
- Cut Watcher System
- Cutting Vibration Dampening System
- Laser Light System
- Shadow Light System
- Spray Mist Lubrication System
- Top Clamp Vising - Input Side
- Top Clamp Vising - Output Side
- 4' Telescoping Table - Input Side
- 4' Telescoping Table - Output Side

www.hemsaw.com

P. O. Box 1148 • Pryor, OK • 74362

Toll Free: (888) 729-7787 • Phone: (918) 825-4821

Fax: (918) 825-4824 • E-Mail: info@hemsaw.com