



Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard. 29 CFR 1910.1200. Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1218-0072

IDENTITY (As Used on Label and List):

Eliminator 104

SECTION I

Manufacturer's Name: HE&M INC. **Emergency Telephone Number:** (314) 614-1449
Address: 4065 S. MAIN & WEBB **Telephone Number for Information:** (918) 825-4821
PRYOR, OK 74362 **Date Prepared:** 07-07-2008

SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

Hazardous Components (Specific Chemical Identity: Common Name(s)) OSHA PEL ACGIH TLV Other Limits Recommended %(opt'l)
NONE

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES

The information in this document is believed to be correct as of the date issued. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OF COMPLETENESS OF THIS INFORMATION. THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition that he assume the risk of his use thereof.

HMIS SYMBOL

SARA Considered— hazardous ingredients void.

HEALTH	1	HMIS	
FLAMABILITY	1	Severe	4
REACTIVITY	0	Serious	3
PERSONAL PROTECTION	A	Moderate	2
		Slight	1
		Minimal	0

SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS

Boiling Point	470°F	Specific Gravity (H2O = 1)	.89
Vapor Pressure (mm Hg.)	N / E	Melting Point	N / A
Vapor Density (AIR = 1)	N / E	Evaporation Rate (Butyl Acetate = 1)	N / A
Solubility in Water:	NO	pH (in water phase)	N / A
Appearance and Odor:	Purple Color —No Odor		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used): 280°F **Flammable Limits** LEL N/E UEL N/E

Extinguishing Media: CO2, Dry Chemical, Foam

Special Fire Fighting Procedures: Do not use water, use self-contained breathing apparatus with a full face piece, in pressure demand.

Unusual Fire and Explosion Hazards: Do not use welding or cutting torch on or near drum even when empty. If improperly reused for other product, it could ignite.

