



**Material Safety Data Sheet**

May be used to comply with OSHA's Hazard Communication Standard. 29 CFR 1910.1200. Standard must be consulted for specific requirements.

**U.S. Department of Labor**

Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1218-0072

**IDENTITY (As Used on Label and List):**

**Eliminator 105**

**SECTION I**

**Manufacturer's Name:** HE&M INC.

**Emergency Telephone Number:** (314) 614-1449

**Address:** 4065 S. MAIN & WEBB  
PRYOR, OK 74362

**Telephone Number for Information:** (918) 825-4821

**Date Prepared:** 07-07-2008

**SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION**

Hazardous Components (Specific Chemical Identity: Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	%(opt'l)
Hexahydro-1,3,5-tris (2-hydroxyethyl)-s-triazine	N/E	N/E	N/E	16
Ethylene Glycol monobutyl ether	N/E	50ppm	N/E	6

**DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES**

The information in this document is believed to be correct as of the date issued. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OF COMPLETENESS OF THIS INFORMATION. THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition that he assume the risk of his use thereof.

**HMIS SYMBOL**

<b>HEALTH</b>	<b>2</b>	HMIS	
<b>FLAMABILITY</b>	<b>0</b>	Severe	4
<b>REACTIVITY</b>	<b>1</b>	Serious	3
<b>PERSONAL PROTECTION</b>	<b>C</b>	Moderate	2
		Slight	1
		Minimal	0

**SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS**

<b>Boiling Point</b>	212°F	<b>Specific Gravity (H<sub>2</sub>O = 1)</b>	1.075
<b>Vapor Pressure (mm Hg.)</b>	N / E	<b>Melting Point</b>	N / E
<b>Vapor Density (AIR = 1)</b>	N / E	<b>Evaporation Rate (Butyl Acetate = 1)</b>	N / E
<b>Solubility in Water:</b>	YES	<b>pH (in water phase)</b>	9.5
<b>Appearance and Odor:</b>	Amber Color -Characteristic Odor		

**SECTION IV - FIRE AND EXPLOSION HAZARD DATA**

<b>Flash Point (Method Used):</b>	N / A	<b>Flammable Limits</b>	LEL	N/E	UEL	N/E
<b>Extinguishing Media:</b>	Not combustible					
<b>Special Fire Fighting Procedures:</b>	None					

**Unusual Fire and Explosion Hazards:** Although not for this product, do not use welding or cutting torch on or near drum even when empty. If improperly reused for other product, it could ignite.

