

P.O. Box 1148 • Pryor, OK 74362
 Phone: (918) 825-4821 • Fax: (918) 825-4824 • Email: coolant@hemsaw.com • Web: www.hemsaw.com

**Experience improved fluid stability and longevity with
 HE&M's enhanced line of metalworking fluids,
 ELIMINATOR II.**

- Multi purpose heavy-duty semi-synthetic formula
- Contains no chlorine, nitrates, phenols or DEA
- Excellent corrosion protection
- Superior resistance to microbial degradation
- Provides quality finishes on machined parts
- Minimal residue
- Low foaming characteristics
- Safe to use on all metals - non staining

Operation	Cast Iron & Carbon Steels	High Alloy Steels & Stainless Steel	Aluminum
Machining, Milling, Drilling, and Turning	1:24-1:19 (4-5%)	1:24-1:19 (4-5%)	1:39-1:32 (2.5-3%)
Form Milling and Sawing	1:24-1:16 (4-6%)	1:19-1:16 (5-6%)	1:39-1:32 (2.5-3%)
Grinding: ID, OD, Centerless	1:32-1:24 (3-4%)	1:32-1:24 (3-4%)	1:32-1:24 (3-4%)

Available In:

P-202000 1 Gallon
 P-202001 4 Gal Case
 P-202005 5 Gal Pail
 P-202055 55 Gal Drum
 P-202275 275 Gal Tote

Physical & Chemical Characteristics:

Appearance/Odor...Amber Liquid/Mild Chemical Odor
 Weight (lb/gal) 8.84
 pH (concentrate) 9.8
 pH (5% dilution) 9.4
 Flash Point None

Dilution Ratio	1:9 (10%)	1:16 (6%)	1:19 (5%)	1:24 (4%)	1:32 (3%)
Refractometer Reading	5.7	3.2	2.7	2.2	1.7