

P.O. Box 1148 • Pryor, OK 74362

Phone: (918) 825-4821 • Fax: (918) 825-4824 • Email: coolant@hemsaw.com • Web: www.hemsaw.com

Eliminator II 213 Hybrid is a semi-synthetic hybrid metalworking fluid formulation that is an excellent replacement for soluble oil applications

- Biostable formulation maintains pH levels and helps to eliminate foul odors
- Small particle size for better dispersion and coverage
- Improved lubricant film strength covers tool surface for increased tool life
- Provides excellent corrosion protection
- Low VOCs for operator acceptance
- Oil rejecting formulation
- Halogen free
- Hard Water stability
- Provides excellent fluid detergency and machine surface cleanliness
- Provides quality finishes on machined parts
- Safe to use on both ferrous and non-ferrous metals

Operation	Carbon Steels, Cast Iron Alloys	Stainless Steel Alloys	Aluminum Alloys
Milling, Drilling, Turning	1:16-1:12 (6-8%)	1:12-1:7 (8-12%)	1:13-1:6 (8-15%)
Reaming, Light Duty Broaching, Milling, Tapping, Sawing	1:13-1:9 (7-10%)	1:10-1:6 (9-15%)	1:10-1:6 (9-15%)
Grinding: ID, OD	1:19-1:13 (5-7%)	1:16-1:9 (6-10%)	1:12-1:7 (8-12%)

Available In:

- P-213000 1 Gallon
- P-213001 4 Gal Case
- P-213005 5 Gal Pail
- P-213055 55 Gal Drum
- P-213275 275 Gal Tote

Physical & Chemical Characteristics:

- Appearance/Odor.....Off-White Liquid/Mild Chemical Odor
- Weight (lb/gal) 8.35
- pH (concentrate) 9.8
- pH (10% dilution) 9.3

Concentration	1:6 (15%)	1:7 (12%)	1:10 (9%)	1:16 (6%)	1:32 (3%)
Refractometer Reading	5.0	4.0	3.0	2.0	1.0