



## Product Description

### Horizontal Pivot Band Saws

#### > Single-Miter Saws

#### >> Cyclone Series

The Cyclone A-C multiple indexes with a 24" bar-feed, saves up to 99 jobs, sawing one job or multiple jobs of differing lengths and quantities in sequence. Each job includes job number, part length and quantity and can miter up to 45° in one direction cutting solids or shapes.

## Standard Features

Easy View Console - All Function Control  
 Computer Controlled Feed System  
 18" Discharge Support  
 Vise - Adjustable Main & Feed  
 Adjustable Clamping Force  
 2 Hold Down Fixtures  
 Vertical Alignment Bar on Bar-Feed  
 Guide Arm - Manual Adjustment  
 Passive "Cut Watcher®" System  
 Variable Blade Speed w/ LED Readout  
 Carbide Blade Guides  
 Manual Blade Tension  
 Adjustable Feed Rate  
 Adjustable Cutting Pressure  
 Coolant System - Flood w/ Wash-Down Hose  
 Blade Brush  
 Broken Blade Function  
 Out-of-Stock Function  
 Safety Guards  
 220V/3PH or 440V/3PH Electrical Motor  
 Requirement - This is Not a Dual Voltage Machine  
 85 PSI, 4-6 CFM Minimum Air Requirement  
 (Equipped w/ Air Filter/Lubricator)

## Technical Specifications

<b>Rectangular Capacity</b>	0-22" W x 0-16" H
<b>Square Capacity</b>	
<b>Round Capacity</b>	
<b>Bar-feed</b>	0-24" (Stroke Air - Multiple Index)
<b>Motor</b>	7.5 HP
<b>Hydraulic Motor</b>	N/A
<b>Operation Type</b>	Automatic
<b>Power Source</b>	Air
<b>Weight</b>	N/A
<b>Blade Type</b>	Bandsaw
<b>Blade Size</b>	16' 0" L x 1.25" H x .042"
<b>Cantilever</b>	
<b>Bandsaw Blade Speed</b>	N/A
<b>Bundle Cut?</b>	Yes

## Optional Features

Top Clamp - Reduced Capacity Main Vise  
 Vise - 3rd on Feed  
 60° Miter Capability (Manual Cut Only)  
 Laser Light System

Top Clamp - Reduced Capacity Feed Vise  
 Full Width Discharge Plate  
 Light Clamping Pressure  
 Air Powered Blade Tension

Spray Mist Lubrication  
5' Idle Roller Stock Table

Single-Phase Voltage  
10' Idle Roller Stock Table

---

**HEMSAW.COM**

**1 (888) 729-7787**