



Product Description

Horizontal Pivot Band Saws

> Single-Miter Saws

>> Cyclone Series

The Cyclone A-C multiple indexes with a 24" bar-feed, saves up to 99 jobs, sawing one job or multiple jobs of differing lengths and quantities in sequence. Each job includes job number, part length and quantity and can miter up to 45° in one direction cutting solids or shapes.

Standard Features

Easy View Console - All Function Control
 Computer Controlled Feed System
 18" Discharge Support
 Vise - Adjustable Main & Feed
 Adjustable Clamping Force
 2 Hold Down Fixtures
 Vertical Alignment Bar on Bar-Feed
 Guide Arm - Manual Adjustment
 Passive "Cut Watcher®" System
 Variable Blade Speed w/ LED Readout
 Carbide Blade Guides
 Manual Blade Tension
 Adjustable Feed Rate
 Adjustable Cutting Pressure
 Coolant System - Flood w/ Wash-Down Hose
 Blade Brush
 Broken Blade Function
 Out-of-Stock Function
 Safety Guards
 220V/3PH or 440V/3PH Electrical Motor
 Requirement - This is Not a Dual Voltage Machine
 85 PSI, 4-6 CFM Minimum Air Requirement
 (Equipped w/ Air Filter/Lubricator)

Technical Specifications

Rectangular Capacity	0-22" W x 0-16" H
Square Capacity	
Round Capacity	
Bar-feed	0-24" (Stroke Air - Multiple Index)
Motor	7.5 HP
Hydraulic Motor	N/A
Operation Type	Automatic
Power Source	Air
Weight	N/A
Blade Type	Bandsaw
Blade Size	16' 0" L x 1.25" H x .042"
Cantilever	
Bandsaw Blade Speed	N/A
Bundle Cut?	Yes

Optional Features

Top Clamp - Reduced Capacity Main Vise
 Vise - 3rd on Feed
 60° Miter Capability (Manual Cut Only)
 Laser Light System

Top Clamp - Reduced Capacity Feed Vise
 Full Width Discharge Plate
 Light Clamping Pressure
 Air Powered Blade Tension

Spray Mist Lubrication
5' Idle Roller Stock Table

Single-Phase Voltage
10' Idle Roller Stock Table

HEMSAW.COM

1 (888) 729-7787