The saw that cuts straight.

CYCLONE M



Technical Specifications

Rectangular Capacity 0-22" W x 0-16" H

Square Capacity

Round Capacity

Bar-feed N/A

Motor 7.5 HP

Hydraulic Motor N/A

Operation Type Semi-Automatic

Power Source Air

Weight N/A

Blade Type Bandsaw

Blade Size 16' 0" L x 1.25" H x .042"

Cantilever

Bandsaw Blade Speed N/A

Bundle Cut? Yes

Product Description

Horizontal Pivot Band Saws

> Single-Miter Saws

>> Cyclone Series

The Cyclone M miters to 60? one direction, is ideal for cutting solids and structural shapes with a 1¼" blade and 7½ HP motor. The control console, mounted on a swing arm, allows semi-automatic sawing and adjustment of Cutting Force, Adjustable Clamping Pressure, and push button Blade Speed.

Standard Features

Easy View Console - Semi-Automatic Control

18" Discharge Support

Vise - Adjustable Main Adjustable Clamping Force

Hold Down Fixture

Guide Arm - Manual Adjustment

Variable Blade Speed w/ LED Readout

Carbide Blade Guides Manual Blade Tension

Adjustable Feed Rate

Adjustable Cutting Pressure

Coolant System - Flood w/ Wash-Down Hose

Blade Brush

Broken Blade Function

Safety Guards

220V/3PH or 440V/3PH Electrical Motor

Requirement - This is Not a Dual Voltage Machine

85 PSI, 4-6 CFM Minimum Air Requirement

(Equipped w/ Air Filter/Lubricator)

Optional Features

Top Clamp - Reduced Capacity Main Vise Full Width Discharge Plate Air Powered Blade Tension

Spray Mist Lubrication 10' Idle Roller Stock Table

24" Roller Load Table Laser Light System Light Clamping Pressure 5' Idle Roller Stock Table Single-Phase Voltage