



Technical Specifications

Rectangular Capacity 0-22" W x 0-22" H

Square Capacity 0-22" (Square)

Round Capacity 0-22" (Diameter)

Bar-feed N/A

Motor 10 HP

Hydraulic Motor 10 HP

Operation Type Semi-Automatic

Power Source Hydraulic

Weight N/A

Blade Type Bandsaw

Blade Size 21' 0" L x 2" H x .063"

Cantilever

Bandsaw Blade Speed N/A

Bundle Cut? No

Product Description

Dual Column Band Saws

> Non-Miter Dual Column Saws

>> DC22 Series

The DC22M band saw is operated using a touch screen that is mounted in a swing-away console. A full-stroking spilt vise that positions automatically with the powered guide arm, patented Cut Watcher® system, and chip auger are standard and many optional features are available.

Standard Features

Swing-Away Control Console w/7" Touch Screen

24" Solid Discharge Table

Full-Stroking Split Main Vise

Adjustable Clamping Force

Carbide Blade Guides

Lead In/Lead Out Roller Guides

Passive "Cut Watcher®" System

Guide Arm Moves in Conjunction w/ Main Vise

Variable Blade Speed w/ Readout on Touch Screen

Powered Blade Tension

Adjustable Feed Rate

Adjustable Cutting Pressure

Chip/Swarf Removal System - Chip Auger

Coolant System - Flood w/ Wash-Down Hose

Blade Brush

Two-Hand Operation Controls

Broken Blade Function

Automatic Blade Idle

Blade Change Interlock

Safety Guards

220V/3PH or 440V/3PH Electrical Motor

Requirement - This is Not a Dual Voltage Machine

Optional Features

Top Clamp - Full Capacity Main Vise Vise - Outboard Powered on Discharge Roller Discharge Table (in Lieu of Solid)

Pedestal Mounted Control Console

Spray Mist Lubrication
Hydraulic Tank Heater
10' Idle Roller Stock Table

Top Clamp - Full Capacity Outboard Vise 36" Roller Load Table w/ Filler Plates

Laser Light System

Roll-Around Control Console

Cold Weather Package

5' Idle Roller Stock Table

10' Powered Roller Stock Table