



Product Description

Dual Column Band Saws

> Non-Miter Dual Column Saws

>> DC26 Series

The H260M-DC operates using touch screen mounted in a swing-away console. The patented Cut Watcher[®] System and Chip Auger are standard features. A full-stroking main vise positions automatically with the powered guide arm, patented Cut Watcher[®] system and Chip Auger are standard and many optional features are available.

Standard Features

Swing-Away Control Console w/ 7" Touch Screen
 24" Solid Discharge Table
 Vise - Full Stroking Main
 Adjustable Clamping Force
 Carbide Blade Guides
 Lead In/Lead Out Roller Guides
 Passive "Cut Watcher[®]" System
 Guide Arm Moves in Conjunction w/ Main Vise
 Variable Blade Speed w/ Readout on Touch Screen
 Powered Blade Tension
 Adjustable Feed Rate
 Adjustable Cutting Pressure
 Coolant System - Flood w/ Wash-Down Hose
 Broken Blade Function
 Two-Hand Operation Controls
 Automatic Blade Idle
 Blade Change Interlock
 220V/3PH or 440V/3PH Electrical Motor
 Requirement - This is Not a Dual Voltage Machine

Technical Specifications

Rectangular Capacity	0-26" W x 0-26" H
Square Capacity	0-26" (Square)
Round Capacity	0-26" (Diameter)
Bar-feed	N/A
Motor	15 HP
Hydraulic Motor	10 HP
Operation Type	Semi-Automatic
Power Source	Hydraulic
Weight	N/A
Blade Type	Bandsaw
Blade Size	22' 0" L x 2" H x .063"
Cantilever	
Bandsaw Blade Speed	N/A
Bundle Cut?	No

Optional Features

Top Clamp - Full Capacity Main Vise
 Vise - Outboard Powered on Discharge w/ Roller Discharge Table
 Chip/Swarf Removal System - Chip Auger
 Spray Mist Lubrication
 Roll-Around Control Console
 Hydraulic Tank Heater

Top Clamp - Full Capacity Outboard Vise
 Roller Discharge Table (in Lieu of Solid)
 Laser Light System
 Pedestal Mounted Control Console
 Cold Weather Package
 5' Idle Roller Stock Table

HEMSAW.COM

1 (888) 729-7787