



Product Description

Dual Column Band Saws

> Non-Miter Dual Column Saws

>> DC30 Series

The DC30A band saw operates using a touch screen control mounted in a swing-away console. A 48" servo twin ball-screw bar-feed is standard and a 120" version is optional. A full-stroking main vise positions automatically with the powered guide arm. The Cut Watcher® System and 3rd Vise on Feed are standard.

Standard Features

- Smart Saw® Control Console w/ 9" Touch Screen
- Industrial IOT Ready - MTConnect Output
- 24" Solid Discharge Table
- Vise - Full Stroking Main & Feed
- Adjustable Clamping Force
- Carbide Blade Guides
- Lead In/Lead Out Roller Guides
- Guide Arm Moves in Conjunction w/ Main Vise
- Variable Blade Speed w/ Readout on Touch Screen
- Passive "Cut Watcher®" System
- Adjustable Feed Rate
- Adjustable Cutting Pressure
- Powered Blade Tension
- Blade Brush
- Coolant System - Flood w/ Wash-Down Hose
- Two-Hand Operation Controls
- Broken Blade Function
- Out-of-Stock Function
- Automatic Blade Idle
- Blade Change Interlock
- Safety Guards
- 220V/3PH or 440V/3PH Electrical Motor
- Requirement - This is Not a Dual Voltage Machine

Technical Specifications

Rectangular Capacity	0-30" W x 0-30" H
Square Capacity	0-30" (Square)
Round Capacity	0-30" (Diameter)
Bar-feed	0-48" (Stroke Servo Twin Ball-Screw - Multiple Index)
Motor	20 HP
Hydraulic Motor	10 HP
Operation Type	Automatic
Power Source	Hydraulic
Weight	N/A
Blade Type	Bandsaw
Blade Size	25' 8" L x 2" H x .063"
Cantilever	
Bandsaw Blade Speed	N/A
Bundle Cut?	No

Optional Features

0-120" Stroke Servo Twin Ball-Screw Bar-Feed w/ 3rd Vise

Bar-Feed Filler Plates

Heavy-Duty Servo Feed

Top Clamp - Full Capacity Main Vise (Increases Remnant Length by 2")

Top Clamp - Full Capacity Feed Vise (Increases
Remnant Length by 3")
Vise - Outboard Powered on Discharge
Servo Controlled Traverse (SCT) - Includes Active
"Cut Watcher®"
Chip/Swarf Removal System - Chip Auger
Pedestal Mounted Control Console
Cold Weather Package
10' Idle Roller Stock Table

Top Clamp - Full Capacity Outboard Vise
Roller Discharge Table (in Lieu of Solid)
Remote Diagnostics
Laser Light System
Roll-Around Control Console
5' Idle Roller Stock Table
10' Powered Roller Stock Table

HEMSAW.COM

1 (888) 729-7787