



Product Description

Dual Column Band Saws

> Non-Miter Dual Column Saws

>> DC30 Series

The DC30M band saw is operated using a touch screen that is mounted in a swing-away console. A full-stroking vise that positions automatically with the powered guide arm, patented Cut Watcher[®] system, and 24' solid discharge table are standard and many optional features are available.

Standard Features

Swing-Away Control Console w/ 7" Touch Screen
24" Solid Discharge Table
Vise - Full Stroking Main
Adjustable Clamping Force
Carbide Blade Guides
Lead In/Lead Out Roller Guides
Passive "Cut Watcher[®]" System
Guide Arm Moves in Conjunction w/ Main Vise
Variable Blade Speed w/ Readout on Touch Screen
Powered Blade Tension
Adjustable Feed Rate
Adjustable Cutting Pressure
Coolant System - Flood w/ Wash-Down Hose
Blade Brush
Two-Hand Operation Controls
Broken Blade Function
Automatic Blade Idle
Blade Change Interlock
Safety Guards
220V/3PH or 440V/3PH Electrical Motor
Requirement - This is Not a Dual Voltage Machine

Technical Specifications

Rectangular Capacity	0-30" W x 0-30" H
Square Capacity	0-30" (Square)
Round Capacity	0-30" (Diameter)
Bar-feed	N/A
Motor	20 HP
Hydraulic Motor	10 HP
Operation Type	Semi-Automatic
Power Source	Hydraulic
Weight	N/A
Blade Type	Bandsaw
Blade Size	23' 0" L x 2" H x .063"
Cantilever	
Bandsaw Blade Speed	N/A
Bundle Cut?	No

Optional Features

Top Clamp - Full Capacity Main Vise
Vise - Outboard Powered on Discharge
Chip/Swarf Removal System - Chip Auger
Pedestal Mounted Control Console
Spray Mist Lubrication
Hydraulic Tank Heater
10' Idle Roller Stock Table

Top Clamp - Full Capacity Outboard Vise
Roller Discharge Table (in Lieu of Solid)
Laser Light System
Roll-Around Control Console
Cold Weather Package
5' Idle Roller Stock Table
10' Powered Roller Stock Table

