



Product Description

Horizontal Pivot Band Saws

> Non-Miter Horizontal Pivot Saws

>> H105 Series

The H105A-C includes a 24" bar-feed and allows multiple indexes and the ability to create and save up to 99 jobs. Each job includes a job number, the part length, and quantity and runs consecutive jobs in sequence.

Standard Features

Easy View Console - All Function Control

Computer Controlled Feed System

24" Solid Discharge Table - Bolts to Saw

Vise - Adjustable Main & Feed

Adjustable Clamping Force

2 Hold Down Fixtures

Vertical Alignment Roller on Bar-Feed

Guide Arm - Manual Adjustment

Passive "Cut Watcher®" System

Variable Blade Speed w/ LED Readout

Carbide Blade Guides

Air Powered Blade Tension

Adjustable Feed Rate

Adjustable Cutting Pressure

Coolant System - Flood w/ Wash-Down Hose

Chip/Swarf Removal System - Chip Auger

Blade Brush

Broken Blade Function

Out-of-Stock Function

Safety Guards

220V/3PH or 440V/3PH Electrical Motor

Requirement - This is Not a Dual Voltage Machine

85 PSI, 4-6 CFM Minimum Air Requirement

(Equipped w/ Air Filter/Lubricator)

Technical Specifications

Rectangular Capacity	0-16" W x 0-14" H
Square Capacity	0-14" (Square)
Round Capacity	0-14" (Diameter)
Bar-feed	0-24" (Stroke Air - Multiple Index)
Motor	7.5 HP
Hydraulic Motor	N/A
Operation Type	Automatic
Power Source	Air
Weight	N/A
Blade Type	Bandsaw
Blade Size	15' 0" L x 1.25" H x .042"
Cantilever	
Bandsaw Blade Speed	N/A
Bundle Cut?	Yes

Optional Features

Top Clamp - Reduced Capacity Main Vise

Vise - 3rd on Feed

Vise - Outboard Powered on Discharge

Spray Mist Lubrication

Top Clamp - Reduced Capacity Feed Vise

Interlocking Vise Jaws

Light Clamping Pressure

Single-Phase Voltage

HEMSAW.COM

1 (888) 729-7787