



Product Description

Horizontal Pivot Band Saws

> Non-Miter Horizontal Pivot Saws

>> H105 Series

The H105A-C includes a 24" bar-feed and allows multiple indexes and the ability to create and save up to 99 jobs. Each job includes a job number, the part length, and quantity and runs consecutive jobs in sequence.

Standard Features

Easy View Console - All Function Control
 Computer Controlled Feed System
 24" Solid Discharge Table - Bolts to Saw
 Vise - Adjustable Main & Feed
 Adjustable Clamping Force
 2 Hold Down Fixtures
 Vertical Alignment Roller on Bar-Feed
 Guide Arm - Manual Adjustment
 Passive "Cut Watcher®" System
 Variable Blade Speed w/ LED Readout
 Carbide Blade Guides
 Air Powered Blade Tension
 Adjustable Feed Rate
 Adjustable Cutting Pressure
 Coolant System - Flood w/ Wash-Down Hose
 Chip/Swarf Removal System - Chip Auger
 Blade Brush
 Broken Blade Function
 Out-of-Stock Function
 Safety Guards
 220V/3PH or 440V/3PH Electrical Motor
 Requirement - This is Not a Dual Voltage Machine
 85 PSI, 4-6 CFM Minimum Air Requirement
 (Equipped w/ Air Filter/Lubricator)

Technical Specifications

Rectangular Capacity	0-16" W x 0-14" H
Square Capacity	0-14" (Square)
Round Capacity	0-14" (Diameter)
Bar-feed	0-24" (Stroke Air - Multiple Index)
Motor	7.5 HP
Hydraulic Motor	N/A
Operation Type	Automatic
Power Source	Air
Weight	N/A
Blade Type	Bandsaw
Blade Size	15' 0" L x 1.25" H x .042"
Cantilever	
Bandsaw Blade Speed	N/A
Bundle Cut?	Yes

Optional Features

Top Clamp - Reduced Capacity Main Vise
 Vise - 3rd on Feed
 Vise - Outboard Powered on Discharge
 Spray Mist Lubrication

Top Clamp - Reduced Capacity Feed Vise
 Interlocking Vise Jaws
 Light Clamping Pressure
 Single-Phase Voltage

HEMSAW.COM

1 (888) 729-7787