



Product Description

Horizontal Pivot Band Saws

> Non-Miter Horizontal Pivot Saws

>> H105 Series

The H105M model includes a 7½ HP motor and a 1¼" blade and will produce straight cuts fast. This saw is perfect for cutting solids and structural shapes. Adjustable clamping pressure and accurate arm control for straight cuts and long blade life.

Standard Features

Easy View Console - Semi-Automatic Control
24" Solid Discharge Table - Bolts to Saw
Vise - Adjustable Main
Adjustable Clamping Force
Hold Down Fixture
Guide Arm - Manual Adjustment
Variable Blade Speed w/ LED Readout
Carbide Blade Guides
Manual Blade Tension
Adjustable Feed Rate
Adjustable Cutting Pressure
Coolant System - Flood w/ Wash-Down Hose
Blade Brush
Broken Blade Function
Safety Guards
220V/3PH or 440V/3PH Electrical Motor
Requirement - This is Not a Dual Voltage Machine
85 PSI, 4-6 CFM Minimum Air Requirement
(Equipped w/ Air Filter/Lubricator)

Technical Specifications

Rectangular Capacity	0-16" W x 0-14" H
Square Capacity	0-14" (Square)
Round Capacity	0-14" (Diameter)
Bar-feed	N/A
Motor	7.5 HP
Hydraulic Motor	N/A
Operation Type	Semi-Automatic
Power Source	Air
Weight	N/A
Blade Type	Bandsaw
Blade Size	15' 0" L x 1.25" H x .042"
Cantilever	
Bandsaw Blade Speed	N/A
Bundle Cut?	Yes

Optional Features

Top Clamp - Reduced Capacity Main Vise
Chip/Swarf Removal System - Chip Auger
Light Clamping Pressure
Spray Mist Lubrication
5' Idle Roller Stock Table

Vise - Outboard Powered on Discharge
Passive "Cut Watcher®" System
Air Powered Blade Tension
Single-Phase Voltage
10' Idle Roller Stock Table