



Product Description

Horizontal Pivot Band Saws

> Non-Miter Horizontal Pivot Saws

>> H130 Series

The H130A is known for rugged and dependable band sawing. The 10 HP motor powers the 1½" blade and a 2 HP hydraulic motor provides adjustable clamping force, powered guide arm, and powered blade tension. A 48" multi-index servo twin ball-screw bar-feed, Cut Watcher® System, and chip auger are standard features.

Standard Features

Control Console w/ 8" Touch Screen
Computer Controlled Feed System
24" Solid Discharge Table - Bolts to Saw
Vises - Full Stroking
Adjustable Clamping Force
Carbide Blade Guides
Roller Guides - Entry & Exit
Guide Arm - Powered
Powered Blade Tension
Passive "Cut Watcher®" System
Variable Blade Speed w/ Readout on Touch Screen
Adjustable Feed Rate
Adjustable Cutting Pressure
Chip/Swarf Removal System - Chip Auger
Coolant System - Flood w/ Wash-Down Hose
Blade Brush
Broken Blade Function
Out-of-Stock Function
Two-Hand Operation Controls
Automatic Blade Idle
Blade Change Interlock
Safety Guards
220V/3PH or 440V/3PH Electrical Motor
Requirement - This is Not a Dual Voltage Machine

Technical Specifications

Rectangular Capacity	0-19" W x 0-10" H
Square Capacity	0-16" (Square)
Round Capacity	0-16" (Diameter)
Bar-feed	0-48" (Stroke Servo Twin Ball-Screw - Multiple Index)
Motor	10 HP
Hydraulic Motor	2 HP
Operation Type	Automatic
Power Source	Hydraulic
Weight	N/A
Blade Type	Bandsaw
Blade Size	17' 0" L x 1.5" H x .050"
Cantilever	
Bandsaw Blade Speed	N/A
Bundle Cut?	Yes

Optional Features

Bar-Feed Filler Plates
Vise - 3rd on Feed
Interlocking Vise Jaws
Laser Light System

Top Clamp - Full Capacity Main & Feed Vise
Vise - Outboard Powered on Discharge
Remote Diagnostics
Pedestal Mounted Control Console

Spray Mist Lubrication
Hydraulic Tank Heater
10' Idle Roller Stock Table

Cold Weather Package
5' Idle Roller Stock Table

HEMSAW.COM

1 (888) 729-7787