



Product Description

Dual Column Band Saws

> Non-Miter Dual Column Saws

>> H130-DC Series

The H130M-DC is operated using a touch screen control mounted in a swing-away console and can be operated in manual or semi-automatic modes. Full stroking variable-pressure vise and powered guide arm are standard along with other features. Many options are available.

Standard Features

Swing-Away Control Console w/ 7" Touch Screen
24" Solid Discharge Table
Vise - Full Stroking Main
Adjustable Clamping Force
Carbide Blade Guides
Lead In/Lead Out Roller Guides
Guide Arm - Powered
Powered Blade Tension
Variable Blade Speed w/ Readout on Touch Screen
Adjustable Feed Rate
Adjustable Cutting Pressure
Coolant System - Flood w/ Wash-Down Hose
Blade Brush
Broken Blade Function
Safety Guards
220V/3PH or 440V/3PH Electrical Motor
Requirement - This is Not a Dual Voltage Machine

Technical Specifications

Rectangular Capacity	0-20" W x 0-20" H
Square Capacity	0-20" (Square)
Round Capacity	0-20" (Diameter)
Bar-feed	N/A
Motor	10 HP
Hydraulic Motor	2 HP
Operation Type	Semi-Automatic
Power Source	Hydraulic
Weight	N/A
Blade Type	Bandsaw
Blade Size	19' 0" L x 1.5" H x .050"
Cantilever	
Bandsaw Blade Speed	N/A
Bundle Cut?	No

Optional Features

Top Clamp - Full Capacity Main Vise
Vise - Outboard Powered on Discharge
Passive "Cut Watcher®" System
Pedestal Mounted Control Console
Hydraulic Tank Heater
Spray Mist Lubrication
5' Discharge Table Extension

Top Clamp - Full Capacity Outboard Vise
Chip/Swarf Removal System - Chip Auger
Laser Light System
Roll-Around Control Console
Cold Weather Package
10' Powered Roller Load Table
10' Discharge Table Extension

10' Powered Discharge Table Extension
10' Idle Roller Stock Table

5' Idle Roller Stock Table
10' Powered Roller Stock Table

HEMSAW.COM

1 (888) 729-7787