

# **H260A-DC**



## **Technical Specifications**

Rectangular Capacity

0-26" W x 0-26" H

**Square Capacity** 

0-26" (Square)

**Round Capacity** 

0-26" (Diameter)

**Bar-feed** 

0-48" (Stroke Servo Twin Ball-

Screw - Multiple Index)

Motor

15 HP

**Hydraulic Motor** 

10 HP

**Operation Type** 

Automatic

**Power Source** 

Hydraulic

Weight

N/A

**Blade Type** 

Bandsaw

**Blade Size** 

22' 0" L x 2" H x .063"

Cantilever

**Bandsaw Blade** 

Speed

N/A

**Bundle Cut?** 

No

### **Optional Features**

0-120" Stroke Servo Twin Ball-Screw Bar-Feed w/

3rd Vise

Bar-Feed Filler Plates

Top Clamp - Full Capacity Feed Vise

**Product Description** 

**Dual Column Band Saws** 

> Non-Miter Dual Column Saws

>> H260-DC Series

The H260-DC band saw operates using a touch screen control mounted in a swing-away console. A 48" servo twin ball-screw bar-feed is standard and a 120" version is optional. A full-stroking main vise positions automatically with the powered guide arm. The Cut Watcher® System and chip auger are standard.

#### **Standard Features**

Smart Saw® Control Console w/ 9" Touch Screen

Industrial IOT Ready - MTConnect Output

24" Solid Discharge Table

Vise - Full Stroking Main & Feed

Adjustable Clamping Force

Carbide Blade Guides

Lead In/Lead Out Roller Guides

Guide Arm Moves in Conjunction w/ Main Vise

Passive "Cut Watcher®" System

Variable Blade Speed w/ Readout on Touch Screen

Powered Blade Tension Adjustable Feed Rate

Adjustable Cutting Pressure

Chip/Swarf Removal System - Chip Auger Coolant System - Flood w/ Wash-Down Hose

Blade Brush

Broken Blade Function Out-of-Stock Function

**Two-Hand Operation Controls** 

Automatic Blade Idle Blade Change Interlock

220V/3PH or 440V/3PH Electrical Motor

Requirement - This is Not a Dual Voltage Machine

Heavy-Duty Servo Feed

Top Clamp - Full Capacity Main Vise Top Clamp - Full Capacity Outboard Vise Vise - 3rd on Feed

Roller Discharge Table (in Lieu of Solid)

Remote Diagnostics Spray Mist Lubrication Roll-Around Control Console Hydraulic Tank Heater 10' Idle Roller Stock Table Vise - Outboard Powered on Discharge w/ Roller

Discharge Table

Servo Controlled Traverse (SCT) - Includes Active

"Cut Watcher®"

Laser Light System

Pedestal Mounted Control Console

Cold Weather Package 5' Roller Stock Table

10' Powered Roller Stock Table

### **HEMSAW.COM**

1 (888) 729-7787