





Product Description

Dual Column Band Saws

> Non-Miter Dual Column Saws

>> H260-DC Series

The H260M-DC operates using touch screen mounted in a swing-away console. The patented Cut Watcher® System and Chip Auger are standard features. A full-stroking main vise positions automatically with the powered guide arm, patented Cut Watcher® system and Chip Auger are standard and many optional features are available.

Technical Specifications

Rectangular Capacity 0-26" W x 0-26" H

Square Capacity 0-26" (Square)

Round Capacity 0-26" (Diameter)

Bar-feed N/A

Motor 15 HP

Hydraulic Motor 10 HP

Operation Type Semi-Automatic

Power Source Hydraulic

Weight N/A

Blade Type Bandsaw

Blade Size 22' 0" L x 2" H x .063"

Cantilever

Bandsaw Blade Speed N/A

Bundle Cut? No

Standard Features

Swing-Away Control Console w/7" Touch Screen

36" Roller Load Table w/ Filler Plates

24" Solid Discharge Table

Vise - Full Stroking Main

Adjustable Clamping Force

Carbide Blade Guides

Lead In/Lead Out Roller Guides

Passive "Cut Watcher®" System

Guide Arm Moves in Conjunction w/ Main Vise

Variable Blade Speed w/ Readout on Touch Screen

Powered Blade Tension

Adjustable Feed Rate

Adjustable Cutting Pressure

Chip/Swarf Removal System - Chip Auger

Coolant System - Flood w/ Wash-Down Hose

Broken Blade Function

Two-Hand Operation Controls

Automatic Blade Idle

Blade Change Interlock

220V/3PH or 440V/3PH Electrical Motor

Requirement - This is Not a Dual Voltage Machine

Optional Features

Top Clamp - Full Capacity Main Vise

Vise - Outboard Powered on Discharge w/ Roller

Discharge Table

Laser Light System

Pedestal Mounted Control Console

Cold Weather Package

5' Idle Roller Stock Table

Top Clamp - Full Capacity Outboard Vise

Roller Discharge Table (in Lieu of Solid)

Spray Mist Lubrication

Roll-Around Control Console

Hydraulic Tank Heater

10' Idle Roller Stock Table

HEMSAW.COM

1 (888) 729-7787