

H260M-DC



Technical Specifications

Rectangular Capacity	0-26" W x 0-26" H
Square Capacity	0-26" (Square)
Round Capacity	0-26" (Diameter)
Bar-feed	N/A
Motor	15 HP
Hydraulic Motor	10 HP
Operation Type	Semi-Automatic
Power Source	Hydraulic
Power Source Weight	Hydraulic N/A
	•
Weight	N/A
Weight Blade Type	N/A Bandsaw
Weight Blade Type Blade Size	N/A Bandsaw 22' 0" L x 2" H x .063"
Weight Blade Type Blade Size Cantilever	N/A Bandsaw 22' 0" L x 2" H x .063"

Product Description

Dual Column Band Saws > Non-Miter Dual Column Saws >> H260-DC Series

The H260M-DC operates using touch screen mounted in a swing-away console. The patented Cut Watcher® System and Chip Auger are standard features. A fullstroking main vise positions automatically with the powered guide arm, patented Cut Watcher® system and Chip Auger are standard and many optional features are available.

Standard Features

Swing-Away Control Console w/7" Touch Screen 36" Roller Load Table w/ Filler Plates 24" Solid Discharge Table Vise - Full Stroking Main Adjustable Clamping Force Carbide Blade Guides Lead In/Lead Out Roller Guides Passive "Cut Watcher®" System Guide Arm Moves in Conjunction w/ Main Vise Variable Blade Speed w/ Readout on Touch Screen Powered Blade Tension Adjustable Feed Rate Adjustable Cutting Pressure Chip/Swarf Removal System - Chip Auger Coolant System - Flood w/ Wash-Down Hose **Broken Blade Function Two-Hand Operation Controls** Automatic Blade Idle Blade Change Interlock 220V/3PH or 440V/3PH Electrical Motor Requirement - This is Not a Dual Voltage Machine

Optional Features

Top Clamp - Full Capacity Main Vise Vise - Outboard Powered on Discharge w/ Roller Discharge Table Laser Light System Pedestal Mounted Control Console Cold Weather Package 5' Idle Roller Stock Table Top Clamp - Full Capacity Outboard Vise

Roller Discharge Table (in Lieu of Solid) Spray Mist Lubrication Roll-Around Control Console Hydraulic Tank Heater 10' Idle Roller Stock Table

HEMSAW.COM

1 (888) 729-7787