



Product Description

Dual Column Band Saws

> Non-Miter Dual Column Saws

>> H3236-DC Series

The H3236M-DC is operated using a touch screen control mounted in a swing-away console and can be operated in manual or semi-automatic modes. Full stroking variable-pressure vise and powered guide arm are standard along with other features. Many options are available.

Standard Features

Swing-Away Control Console w/ 7" Touch Screen
24" Roller Discharge Table
Vise - Full Stroking Main
Adjustable Clamping Force
Carbide Blade Guides
Lead In/Lead Out Roller Guides
Passive "Cut Watcher®" System
Guide Arm - Powered
Variable Blade Speed w/ Readout on Touch Screen
Adjustable Feed Rate
Adjustable Cutting Pressure
Powered Blade Tension
Coolant System - Flood w/ Wash-Down Hose
Blade Brush
Broken Blade Function
Two-Hand Operation Controls
Automatic Blade Idle
Safety Guards
Blade Change Interlock
220V/3PH or 440V/3PH Electrical Motor
Requirement - This is Not a Dual Voltage Machine

Technical Specifications

Rectangular Capacity	0-36" W x 0-32" H
Square Capacity	0-32" (Square)
Round Capacity	0-32" (Diameter)
Bar-feed	N/A
Motor	20 HP
Hydraulic Motor	5 HP
Operation Type	Semi-Automatic
Power Source	Hydraulic
Weight	N/A
Blade Type	Bandsaw
Blade Size	27' 0" L x 2" H x .063"
Cantilever	
Bandsaw Blade Speed	N/A
Bundle Cut?	No

Optional Features

Top Clamp - Full Capacity Main Vise
Vise - Outboard Powered on Discharge
Chip/Swarf Removal System - Chip Conveyor
Shadow Light System
Pedestal Mounted Control Console
Cold Weather Package
10' Idle Roller Load Table

Top Clamp - Full Capacity Outboard Vise
2-5/8" Blade Option - HD Gear Box
Laser Light System
Spray Mist Lubrication
Roll-Around Control Console
Hydraulic Tank Heater
10' Powered Roller Load Table

5' Discharge Table Extension
10' Powered Discharge Table Extension
10' Idle Roller Stock Table

10' Discharge Table Extension
5' Idle Roller Stock Table
10' Powered Roller Stock Table

HEMSAW.COM

1 (888) 729-7787