





## **Technical Specifications**

| Rectangular<br>Capacity | 0-12.75" W x 0-12.75" H                |
|-------------------------|--|
| Square Capacity         | 0-12" (Square)                         |
| Round Capacity          | 0-12.75" (Diameter)                    |
| Bar-feed                | 0-24" (Stroke Air - Multiple<br>Index) |
| Motor                   | 3 HP                                   |
| Hydraulic Motor         | N/A                                    |
| <b>Operation Type</b>   | Automatic                              |
| <b>Power Source</b>     | Air                                    |
| Weight                  | N/A                                    |
| Blade Type              | Bandsaw                                |
| Blade Size              | 12' 10" L x 1" H x .035"               |
| Cantilever              |  |
| Bandsaw Blade<br>Speed  | N/A                                    |
| <b>Bundle Cut?</b>      | Yes                                    |

# **Optional Features**

Vise - 3rd on Feed Top Clamp - Reduced Capacity Feed Vise Light Clamping Pressure 5' Idle Roller Stock Table

### **Product Description**

#### Horizontal Pivot Band Saws > Non-Miter Horizontal Pivot Saws >> H90 Series

The H90A-C includes a 24" bar-feed, allows multiple indexes, and the ability to create and save up to 99 jobs. Each job includes a job number, part length, and quantity and it runs consecutive job numbers in sequence. The H90A-C produces fast accurate cuts on small solids and shapes.

### **Standard Features**

Easy View Console - All Function Control Computer Controlled Feed System 24" Solid Discharge Table - Bolts to Saw Vise - Adjustable Main & Feed Adjustable Clamping Force 2 Hold Down Fixtures Guide Arm - Manual Adjustment Passive "Cut Watcher®" System Variable Blade Speed w/ LED Readout Carbide Blade Guides Manual Blade Tension Adjustable Feed Rate Adjustable Cutting Pressure Coolant System - Flood w/ Wash-Down Hose Vertical Alignment Bar on Bar-Feed Blade Brush **Broken Blade Function Out-of-Stock Function** Safety Guards 220V/3PH or 440V/3PH Electrical Motor Requirement - This is Not a Dual Voltage Machine 85 PSI, 4-6 CFM Minimum Air Requirement (Equipped w/ Air Filter/Lubricator)

Interlocking Vise Jaws Top Clamp - Reduced Capacity Main Vise Spray Mist Lubrication 10' Idle Roller Stock Table

### **HEMSAW.COM**

# 1 (888) 729-7787