



Technical Specifications

RectangularCapacity

0-12.75" W x 0-12.75" H

Square Capacity 0-12" (Square)

Round Capacity 0-12.75" (Diameter)

Bar-feed 0-24" (Stroke Air - Multiple

Index)

Motor 3 HP

Hydraulic Motor N/A

Operation Type Automatic

Power Source Air

Weight N/A

Blade Type Bandsaw

Blade Size 12' 10" L x 1" H x .035"

Cantilever

Bandsaw Blade

Speed N/A

Bundle Cut? Yes

Product Description

Horizontal Pivot Band Saws

> Non-Miter Horizontal Pivot Saws

>> H90 Series

The H90A-C includes a 24" bar-feed, allows multiple indexes, and the ability to create and save up to 99 jobs. Each job includes a job number, part length, and quantity and it runs consecutive job numbers in sequence. The H90A-C produces fast accurate cuts on small solids and shapes.

Standard Features

Easy View Console - All Function Control

Computer Controlled Feed System

24" Solid Discharge Table - Bolts to Saw

Vise - Adjustable Main & Feed Adjustable Clamping Force

2 Hold Down Fixtures

Guide Arm - Manual Adjustment Passive "Cut Watcher®" System

Variable Blade Speed w/ LED Readout

Carbide Blade Guides

Manual Blade Tension Adjustable Feed Rate

Adjustable Cutting Pressure

Coolant System - Flood w/ Wash-Down Hose

Vertical Alignment Bar on Bar-Feed

Blade Brush

Broken Blade Function

Out-of-Stock Function

Safety Guards

220V/3PH or 440V/3PH Electrical Motor

Requirement - This is Not a Dual Voltage Machine

85 PSI, 4-6 CFM Minimum Air Requirement

(Equipped w/ Air Filter/Lubricator)

Optional Features

Vise - 3rd on Feed Top Clamp - Reduced Capacity Feed Vise Light Clamping Pressure 5' Idle Roller Stock Table Interlocking Vise Jaws
Top Clamp - Reduced Capacity Main Vise
Spray Mist Lubrication
10' Idle Roller Stock Table

HEMSAW.COM

1 (888) 729-7787