

KTC-100NF



Product Description

Circular Saws

> CNC Aluminum Saws

The KTC-100NF automatic carbide sawing machine cuts non-ferrous material. The saw head is servomotor driven and the hydraulics are hard-plumbed for consistent operation. Automatic workpiece loading and part sorting are standard features. The stroking outboard vise provides short remnants, horizontal and vertical vises are included. Options are available.

Technical Specifications

Rectangular Capacity

Square Capacity 0-3.149" (Square)

Round Capacity 0-3.937" (Diameter)

Bar-feed N/A

Motor 15 HP

Hydraulic Motor 3 HP

Operation Type Automatic

Power Source Hydraulic

Weight N/A

Blade Type Circular

Primary Circular 355mm Diameter --- [5859-

Blade 14648 RPM]

Bundle Cut? No

Standard Features

Uses TCT Carbide Tipped Saw Blade 355 x 2.0t mm

Blade Feed Pivot Type

Compact PLC Control & Inverter

Touch Screen Feature for Setting Machine & Cut

Functions

Saw Blade Feed Driven by Servo Motor

Hard-Plumbed Hydraulic System

Vise - Hydraulic Horizontal & Vertical Main

Stroking Front "Outboard" Vise (Reduces Remnant

Lengths)

20' Standard Loader - Automatic Workpiece Loading

Automatic Product Sorting Work Piece Positioning Precision Spindle Variable Blade Speed

Magnetic Power Brake and Fan

Blade Brush

Chip Removal - Air Gun & Vacuum Dust Removal

Built-In Coolant System w/ Flood & Mist

208-240V, 50/60hz, 3-Phase

Optional Features

10' Standard Loader Extention (up to 60' total) 10' Bundle Loader Extention (up to 60' total)

Sliding Aid

Mist Collection System

20' Bundle Loader Unloading Device

Large Vacuum Dust Collector