



## **Technical Specifications**

**Rectangular** 0-25" W x 0-25" H x 144"

**Capacity** 

**Square Capacity** 0-25" (Square)

**Round Capacity** 

Bar-feed N/A

Motor 20 HP

**Hydraulic Motor** 2 HP

**Operation Type** Semi-Automatic

**Power Source** Hydraulic

Weight N/A

vicigit 14/15

Blade Type Bandsaw

**Blade Size** 19' 10" L x 1.5" H x .050"

N/A

Cantilever

**Bandsaw Blade** 

**Speed** 

**Bundle Cut?** No

## **Product Description**

**Plate Saws** 

> Moving Material Saws

The PM25-144 is a moving material saw using the ECT System. The rigidity of the fixed arm produces straighter cuts for up to 12' plates. It includes a laser light for material alignment and the Cut Watcher® System. A touch screen is used for settings, functions, and diagnostics.

## **Standard Features**

Computerized Control of Table Travel Control Console w/ 9" Touch Screen

Industrial IOT Ready - MTConnect Output

Electronic Controlled Traverse (Controls Feed Rate &

Cutting Force)

H-Beam Construction on Table

Variable Blade Speed w/ Readout on Touch Screen

Carbide Blade Guides Guide Arm - Powered

Passive "Cut Watcher®" System

Powered Blade Tension Laser Light System

Chip/Swarf Removal System - Chip Conveyor

Partial Catwalk

Coolant System - Flood w/ Wash-Down Hose

**Two-Hand Operation Controls** 

Automatic Blade Idle Broken Blade Function

Blade Brush

Blade Change Interlock

Safety Guards

220V/3PH or 440V/3PH Electrical Motor

Requirement - This is Not a Dual Voltage Machine

## **Optional Features**

Remote Diagnostics

Hydraulic Tank Heater

Servo Controlled Traverse (SCT) - Includes Active

"Cut Watcher®"

Cold Weather Package