



Product Description

Horizontal Pivot Band Saws

> Single-Miter Saws

>> Sidewinder Series

The Sidewinder M saw cuts miters up to 60° in one direction and is ideal for cutting small solids and structural shapes. The control allows semi-automatic sawing with the Cutting Force, adjustable Clamping Pressure, and push button Blade Speed simple to adjust. Many options are available.

Standard Features

Easy View Console - Semi-Automatic Control
18" Discharge Support
Vise - Adjustable Main
Adjustable Clamping Force
Hold Down Fixture
Manual Adjustable Guide Arm
Variable Blade Speed w/ LED Readout
Manual Blade Tension
Carbide Blade Guides
Adjustable Feed Rate
Adjustable Cutting Pressure
Coolant System - Flood w/ Wash-Down Hose
Blade Brush
Broken Blade Function
Safety Guards
220V/3PH or 440V/3PH Electrical Motor
Requirement - This is Not a Dual Voltage Machine
85 PSI, 4-6 CFM Minimum Air Requirement
(Equipped w/ Air Filter/Lubricator)

Technical Specifications

Rectangular Capacity 0-16" W x 0-12.75" H

Square Capacity

Round Capacity

Bar-feed N/A

Motor 3 HP

Hydraulic Motor N/A

Operation Type Semi-Automatic

Power Source Air

Weight N/A

Blade Type Bandsaw

Blade Size 13' 6" L x 1" H x .035"

Cantilever

Bandsaw Blade Speed N/A

Bundle Cut? Yes

Optional Features

Top Clamp - Reduced Capacity Main Vise
Light Clamping Pressure
Spray Mist Lubrication
10' Idle Roller Stock Table

Full Width Discharge Plate
Laser Light System
5' Roller Stock Table
Single-Phase Voltage