



Product Description

Vertical Band Saws

> Vertical Double-Miter Saws

>> V/VT140 Series

The V140 and VT140HM-60-CTS band saws vary from a vertical blade orientation on the V140 to a forward-canting blade on the VT140 version. The touch screen control, mounted in a swing-away console, allows the operator to enter an angle and the arm will travel to that position and stop.

Standard Features

Swing-Away Control Console w/ 7" Touch Screen
Powered Programmable Tilt w/ Angle Readout
Vise - Full Stroking Main
Adjustable Clamping Force
Carbide Blade Guides
Guide Arm - Powered
Variable Blade Speed w/ Readout on Touch Screen
Electronic Controlled Traverse (Controls Feed Rate & Cutting Force)
Idle Base Rollers - 1 Each Side of Base
Powered Blade Tension
Forward Cut Stop
Coolant System - Flood w/ Wash-Down Hose
Blade Brush
Broken Blade Function
Blade Change Interlock
Safety Guards
220V/3PH or 440V/3PH Electrical Motor
Requirement - This is Not a Dual Voltage Machine

Technical Specifications

Rectangular Capacity	0-24" W x 0-31" H
Square Capacity	0-24" (Square)
Round Capacity	0-24" (Diameter)
Bar-feed	N/A
Motor	10 HP
Hydraulic Motor	5 HP
Operation Type	Semi-Automatic
Power Source	Hydraulic
Weight	N/A
Blade Type	Bandsaw
Blade Size	20' 0" L x 1.5" H x .050"
Cantilever	Fixed
Bandsaw Blade Speed	N/A
Bundle Cut?	Yes

Optional Features

Swing-Away Top Clamp - Main Vise
Vise - 2nd Main
Laser Light System

Chip/Swarf Removal System - Chip Conveyor
Spray Mist Lubrication
5' Roller Load Table

Top Clamp - Reduced Capacity Main Vise
Passive "Cut Watcher®" System
Power Raised Lift Up Rollers
Chip/Swarf Removal System - Manual Hand-Crank
Chip Conveyor
Pedestal Mounted Control Console
10' Idle Roller Load Table

10' Powered Roller Load Table
10' Roller Discharge Table
5' Idle Roller Stock Table
10' Powered Roller Stock Table

5' Roller Discharge Table
10' Powered Roller Discharge Table
10' Idle Roller Stock Table

HEMSAW.COM

1 (888) 729-7787