



## Product Description

### Vertical Band Saws

#### > Vertical Double-Miter Saws

#### >> V/VT200 Series

The V200HM-CTS band saw is operated by a touch screen control that is located in a swing-away console at the front of the saw and allows the operator to enter an angle and the arm will travel to that position and stop.

## Standard Features

Swing-Away Control Console w/ 7" Touch Screen  
Powered Programmable Tilt w/ Angle Readout  
Vise - Full Stroking Main & 2nd Main  
Adjustable Clamping Force  
Broken Blade Function  
Carbide Blade Guides  
Guide Arm - Powered  
Electronic Controlled Traverse (Controls Feed Rate & Cutting Force)  
Variable Blade Speed w/ Readout on Touch Screen  
Forward Cut Stop  
Power Raised Lift Up Rollers  
Powered Blade Tension  
Chip/Swarf Removal System - Chip Conveyor  
Coolant System - Flood w/ Wash-Down Hose  
Blade Brush  
Blade Change Interlock  
Safety Guards  
220V/3PH or 440V/3PH Electrical Motor  
Requirement - This is Not a Dual Voltage Machine

## Technical Specifications

<b>Rectangular Capacity</b>	0-25" W x 0-36" H
<b>Square Capacity</b>	0-25" (Square)
<b>Round Capacity</b>	0-25" (Diameter)
<b>Bar-feed</b>	N/A
<b>Motor</b>	15 HP
<b>Hydraulic Motor</b>	5 HP
<b>Operation Type</b>	Semi-Automatic
<b>Power Source</b>	Hydraulic
<b>Weight</b>	N/A
<b>Blade Type</b>	Bandsaw
<b>Blade Size</b>	20' 6" L x 2" H x .063"
<b>Cantilever</b>	
<b>Bandsaw Blade Speed</b>	N/A
<b>Bundle Cut?</b>	Yes

## Optional Features

Swing-Away Top Clamp - Main Vise  
Passive "Cut Watcher®" System  
Roll-Around Control Console  
Spray Mist Lubrication  
10' Idle Roller Load Table  
10' Roller Discharge Table

Laser Light System  
Pedestal Mounted Control Console  
Right to Left Feed Direction  
5' Roller Load Table  
5' Roller Discharge Table

