



## Product Description

### Vertical Band Saws

> Vertical Double-Miter Saws

>> V/VT200 Series

The V200HM-CTS band saw is operated by a touch screen control that is located in a swing-away console at the front of the saw and allows the operator to enter an angle and the arm will travel to that position and stop.

## Standard Features

Swing-Away Control Console w/ 7" Touch Screen  
 Powered Programmable Tilt w/ Angle Readout  
 Vise - Full Stroking Main & 2nd Main  
 Adjustable Clamping Force  
 Broken Blade Function  
 Carbide Blade Guides  
 Guide Arm - Powered  
 Electronic Controlled Traverse (Controls Feed Rate & Cutting Force)  
 Variable Blade Speed w/ Readout on Touch Screen  
 Forward Cut Stop  
 Power Raised Lift Up Rollers  
 Powered Blade Tension  
 Chip/Swarf Removal System - Chip Conveyor  
 Coolant System - Flood w/ Wash-Down Hose  
 Blade Brush  
 Blade Change Interlock  
 Safety Guards  
 220V/3PH or 440V/3PH Electrical Motor  
 Requirement - This is Not a Dual Voltage Machine

## Technical Specifications

<b>Rectangular Capacity</b>	0-25" W x 0-36" H
<b>Square Capacity</b>	0-25" (Square)
<b>Round Capacity</b>	0-25" (Diameter)
<b>Bar-feed</b>	N/A
<b>Motor</b>	15 HP
<b>Hydraulic Motor</b>	5 HP
<b>Operation Type</b>	Semi-Automatic
<b>Power Source</b>	Hydraulic
<b>Weight</b>	N/A
<b>Blade Type</b>	Bandsaw
<b>Blade Size</b>	20' 6" L x 2" H x .063"
<b>Cantilever</b>	
<b>Bandsaw Blade Speed</b>	N/A
<b>Bundle Cut?</b>	Yes

## Optional Features

Swing-Away Top Clamp - Main Vise  
 Passive "Cut Watcher®" System  
 Roll-Around Control Console  
 Spray Mist Lubrication  
 10' Idle Roller Load Table  
 10' Roller Discharge Table

Laser Light System  
 Pedestal Mounted Control Console  
 Right to Left Feed Direction  
 5' Roller Load Table  
 5' Roller Discharge Table

