

VT100HLM-60-CTS



Technical Specifications

Rectangular Capacity 0-18" W x 0-20.75" H

Square Capacity 0-18" (Square)

Round Capacity 0-18" (Diameter)

Bar-feed N/A

Motor 5 HP

Hydraulic Motor 2 HP

Operation Type Semi-Automatic

Power Source Hydraulic

Weight N/A

Blade Type Bandsaw

Blade Size 15' 6" L x 1.25" H x .042"

Cantilever Removable

Bandsaw Blade Speed N/A

Bundle Cut? Yes

Product Description

Vertical Band Saws

> Vertical Double-Miter Saws

>> V/VT100 Series

The VT100HLM-60-CTS miters up to 60? in both directions. The control console is located in a swingaway console at the front of the saw. A touch screen is used to operate the various functions on the saw. Optional vises and other features are available.

Standard Features

Swing-Away Control Console w/7" Touch Screen

4° Removable Arm Cant

Powered Programmable Tilt w/ Angle Readout

Vise - Full Stroking Main

Adjustable Clamping Force

Carbide Blade Guides

Guide Arm - Powered

Variable Blade Speed w/ Readout on Touch Screen

Electronic Controlled Traverse (Controls Feed Rate &

Cutting Force)

Powered Blade Tension

Forward Cut Stop

Coolant System - Flood w/ Wash-Down Hose

Boltable Side Wings for Coolant Drainage

Blade Brush

Broken Blade Function

Safety Guards

220V/3PH or 440V/3PH Electrical Motor

Requirement - This is Not a Dual Voltage Machine

Optional Features

Swing-Away Top Clamp - Main Vise

Vise - 2nd Main

Power Raised Lift Up Rollers

Laser Light System

Spray Mist Lubrication

10' Idle Roller Load Table 10' Roller Discharge Table Top Clamp - Reduced Capacity Main Vise

Passive "Cut Watcher®" System

12" H Wear Plates - Non Mitered

Pedestal Mounted Control Console

5' Roller Load Table

5' Roller Discharge Table

5' Idle Roller Stock Table

HEMSAW.COM

1 (888) 729-7787