



Technical Specifications

Rectangular Capacity	0-18" W x 0-24" H
Square Capacity	0-18" (Square)
Round Capacity	0-18" (Diameter)
Bar-feed	0-48" (Stroke Hydraulic Motor - Multiple Index)
Motor	7.5 HP
Hydraulic Motor	5 HP
Operation Type	Automatic
Power Source	Hydraulic
Weight	N/A
Blade Type	Bandsaw
Blade Size	16' 6" L x 1.25" H x .042"
Cantilever	Fixed
Bandsaw Blade Speed	N/A
Bundle Cut?	Yes

Optional Features

0-48" Stroke Servo Twin Ball-Screw Bar-Feed0-120" Stroke Servo Twin Ball-Screw Bar-Feed w/
3rd ViseBar-Feed Filler PlatesSwing-Away Top Clamp - Main ViseTop Clamp - Full Capacity Feed ViseTop Clamp - Reduced Capacity Main Vise

VT120HA-60-CTS

Product Description

Vertical Band Saws > Vertical Double-Miter Saws >> V/VT120 Series

The VT120HA-60-CTS miters to 60? in both directions. The saw can retain jobs by job number saving size and quantity. Included is the patented Cut Watcher® and the Blade Saver feature. The 48" hydraulic bar-feed is standard and optional are 48" or 120" servo-driven twin ball screw bar-feeds.

Standard Features

Swing-Away Control Console w/ 8" Touch Screen Computer Controlled Feed System Powered Programmable Tilt w/ Angle Readout Vise - Full Stroking Main & Feed Adjustable Clamping Force Carbide Blade Guides Variable Blade Speed w/ Readout on Touch Screen Guide Arm - Powered Electronic Controlled Traverse (Controls Feed Rate & Cutting Force) Passive "Cut Watcher®" System Powered Blade Tension Blade Saver Forward Cut Stop Idle Base Rollers - 1 Each Side of Base Coolant System - Flood w/ Wash-Down Hose Blade Brush **Out-of-Stock Function Broken Blade Function** Safety Guards 220V/3PH or 440V/3PH Electrical Motor Requirement - This is Not a Dual Voltage Machine

Top Clamp - Reduced Capacity Feed Vise Vise - 3rd on Feed Laser Light System Chip/Swarf Removal System - Manual Hand-Crank Chip Conveyor Pedestal Mounted Control Console Cold Weather Package 5' Roller Discharge Table 10' Clutched Powered Discharge Table 10' Idle Roller Stock Table

HEMSAW.COM

Vise - 2nd Main Power Raised Lift Up Rollers Chip/Swarf Removal System - Chip Conveyor

Right to Left Feed Direction Spray Mist Lubrication Hydraulic Tank Heater 10' Roller Discharge Table 5' Idle Roller Stock Table 10' Powered Roller Stock Table

1 (888) 729-7787