



Technical Specifications

Rectangular Capacity	0-18" W x 0-24" H
Square Capacity	0-18" (Square)
Round Capacity	0-18" (Diameter)
Bar-feed	N/A
Motor	7.5 HP
Hydraulic Motor	5 HP
Operation Type	Semi-Automatic
Power Source	Hydraulic
Weight	N/A
Blade Type	Bandsaw
Blade Size	16' 6" L x 1.25" H x .042"
Cantilever	Fixed
Bandsaw Blade Speed	N/A
Bundle Cut?	Yes

VT120HM-60-CTS

Product Description

Vertical Band Saws > Vertical Double-Miter Saws >> V/VT120 Series

The VT120HM-60-CTS miters up to 60? in both directions. The control console is located in a swing-away console at the front of the saw. A touch screen is used to operate the various functions on the saw. Optional vises and other features are available.

Standard Features

Swing-Away Control Console w/7" Touch Screen Powered Programmable Tilt w/ Angle Readout Vise - Full Stroking Main Adjustable Clamping Force Variable Blade Speed w/ Readout on Touch Screen Carbide Blade Guides Guide Arm - Powered Electronic Controlled Traverse (Controls Feed Rate & Cutting Force) Powered Blade Tension Idle Base Rollers - 1 Each Side of Base Forward Cut Stop Coolant System - Flood w/ Wash-Down Hose Blade Brush **Broken Blade Function** Safety Guards 220V/3PH or 440V/3PH Electrical Motor Requirement - This is Not a Dual Voltage Machine

Optional Features

Vise - 2nd Main Top Clamp - Reduced Capacity Main Vise

Laser Light System Power Raised Lift Up Rollers Spray Mist Lubrication Cold Weather Package Swing-Away Top Clamp - Main Vise Passive "Cut Watcher®" System Chip/Swarf Removal System - Manual Hand-Crank Chip Conveyor Powered Chip Conveyor Pedestal Mounted Control Console Hydraulic Tank Heater 5' Roller Load Table 5' Roller Discharge Table 10' Powered Roller Discharge Table 10' Idle Roller Stock Table

HEMSAW.COM

10' Powered Roller Load Table10' Roller Discharge Table5' Idle Roller Stock Table

1 (888) 729-7787