



Product Description

Vertical Band Saws

> Vertical Double-Miter Saws

>> V/VT200 Series

The VT200HM-CTS band saw is operated by a touch screen control that is located in a swing-away console at the front of the saw and allows the operator to enter an angle and the arm will travel to that position and stop. The arm has a forward cant.

Standard Features

Swing-Away Control Console w/ 7" Touch Screen
Powered Programmable Tilt w/ Angle Readout
Vise - Full Stroking Main & 2nd Main
Adjustable Clamping Force
Carbide Blade Guides
Guide Arm - Powered
Electronic Controlled Traverse (Controls Feed Rate & Cutting Force)
Variable Blade Speed w/ Readout on Touch Screen
Forward Cut Stop
Powered Blade Tension
Chip/Swarf Removal System - Chip Conveyor
Power Raised Lift Up Rollers
Coolant System - Flood w/ Wash-Down Hose
Blade Brush
Broken Blade Function
Blade Change Interlock
Safety Guards
220V/3PH or 440V/3PH Electrical Motor
Requirement - This is Not a Dual Voltage Machine

Technical Specifications

Rectangular Capacity	0-25" W x 0-36" H
Square Capacity	0-25" (Square)
Round Capacity	0-25" (Diameter)
Bar-feed	N/A
Motor	15 HP
Hydraulic Motor	5 HP
Operation Type	Semi-Automatic
Power Source	Hydraulic
Weight	N/A
Blade Type	Bandsaw
Blade Size	24' 8" L x 2" H x .063"
Cantilever	Fixed
Bandsaw Blade Speed	N/A
Bundle Cut?	Yes

Optional Features

Swing-Away Top Clamp - Main Vise
Passive "Cut Watcher®" System
Pedestal Mounted Control Console
Hydraulic Tank Heater
10' Roller Discharge Table
10' Powered Roller Stock Table

Laser Light System
Spray Mist Lubrication
Cold Weather Package
5' Roller Discharge Table
5' Roller Load Table

