

WF160LA



Technical Specifications

Rectangular Capacity	0-30" W x 0-25" H
Square Capacity	0-25" (Square)
Round Capacity	0-25" (Diameter)
Bar-feed	0-48" (Stroke Servo Twin Ball- Screw - Multiple Index)
Motor	15 HP
Hydraulic Motor	5 HP
Operation Type	Automatic
Power Source	Hydraulic
Weight	N/A
Blade Type	Bandsaw
Blade Size	26' 9" L x 2" H x .063"
Cantilever	
Bandsaw Blade Speed	N/A
Bundle Cut?	Yes

Product Description

Dual Column Band Saws > Wide Flange/Bundle Saws >> WF160 Series

The WF160A Smart Saw includes a touch screen control mounted in a swing away console. The multi-index 48" twin ball-screw servo-driven barfeed and bi-directional vises are standard. The 9.2? fixed blade cant is designed to cut structural shapes and bundles. Many options include additional clamps and 120" bar-feed.

Standard Features

Smart Saw® Control Console w/ 9" Touch Screen Industrial IOT Ready - MTConnect Output Arm Cant - 9.2° Permanent 24" Roller Discharge Table Vise - Full Stroking Bi-Directional Main & Feed Adjustable Clamping Force Vise - 3rd Bi-Directional on Feed Carbide Blade Guides Lead In/Lead Out Roller Guides Guide Arm - Powered Passive "Cut Watcher®" System Variable Blade Speed w/ Readout on Touch Screen Adjustable Feed Rate Adjustable Cutting Pressure Powered Blade Tension Chip/Swarf Removal System - Chip Conveyor Coolant System - Flood w/ Wash-Down Hose Blade Brush **Two-Hand Operation Controls** Automatic Blade Idle **Broken Blade Function Out-of-Stock Function** Blade Change Interlock Safety Guards 220V/3PH or 440V/3PH Electrical Motor Requirement - This is Not a Dual Voltage Machine

Optional Features

0-120" Stroke Servo Twin Ball-Screw Bar-Feed w/ 3rd Vise Bar-Feed Filler Plates Top Clamp - Full Capacity Main & Feed Vise

Heavy-Duty Servo Feed 2-5/8" Blade Option - HD Gear Box Top Clamp - Full Capacity Main Vise Top Clamp - Full Capacity Outboard Vise Vise - Bi-Directional Outboard Laser Light System Cold Weather Package Roll-Around Control Console 10' Discharge Table Extension 5' Idle Roller Stock Table 10' Powered Roller Stock Table

HEMSAW.COM

Servo Controlled Traverse (SCT) - Includes Active "Cut Watcher®"

Remote Diagnostics Spray Mist Lubrication Pedestal Mounted Control Console Hydraulic Tank Heater 5' Discharge Table Extension 10' Idle Roller Stock Table

1 (888) 729-7787