





Technical Specifications

Rectangular Capacity 0-27" W x 0-18" H

Square Capacity 0-18" (Square)

Round Capacity 0-18" (Diameter)

Bar-feed N/A

Motor 10 HP

Hydraulic Motor 5 HP

Operation Type Semi-Automatic

Power Source Hydraulic

Weight N/A

Blade Type Bandsaw

Blade Size 21' 0" L x 1.5" H x .050"

Cantilever Fixed

Bandsaw Blade Speed N/A

Bundle Cut? Yes

Product Description

Dual Column Band Saws
> Wide Flange/Bundle Saws

>> WF1827 Series

The WF1827M band saw is designed to cut structural shapes and bundles efficiently using a fixed 9.2? canted blade. Operated with a touch-screen control mounted in a swing-away console it includes a full-stroking bi-directional main vise. Many options are available including additional top clamps and outboard vise.

Standard Features

Swing-Away Control Console w/7" Touch Screen

24" Roller Discharge Table

Vise - Full Stroking Bi-Directional Main

Adjustable Clamping Force Arm Cant - 9.2° Permanent Carbide Blade Guides

Lead In/Lead Out Roller Guides

Guide Arm - Powered

Variable Blade Speed w/ Readout on Touch Screen

Adjustable Feed Rate Adjustable Cutting Pressure Powered Blade Tension

Coolant System - Flood w/ Wash-Down Hose

Two-Hand Operation Controls

Blade Brush

Broken Blade Function Automatic Blade Idle Blade Change Interlock

Safety Guards

220V/3PH or 440V/3PH Electrical Motor

Requirement - This is Not a Dual Voltage Machine

Optional Features

Top Clamp - Full Capacity Main Vise

Vise - Bi-Directional Outboard

Chip/Swarf Removal System - Chip Conveyor

Spray Mist Lubrication

Pedestal Mounted Control Console

Hydraulic Tank Heater

10' Idle Roller Load Table

Top Clamp - Full Capacity Outboard Vise

Passive "Cut Watcher®" System

Laser Light System

Dual Spray Mist Lubrication - Flood/Mist Selector

Switch

Roll-Around Control Console

Cold Weather Package

5' Discharge Table Extension

HEMSAW.COM

1 (888) 729-7787