





## **Technical Specifications**

**Rectangular Capacity** 0-27" W x 0-18" H

**Square Capacity** 0-18" (Square)

**Round Capacity** 0-18" (Diameter)

**Bar-feed** N/A

Motor 10 HP

**Hydraulic Motor** 5 HP

**Operation Type** Semi-Automatic

**Power Source** Hydraulic

Weight N/A

**Blade Type** Bandsaw

**Blade Size** 21' 0" L x 1.5" H x .050"

**Cantilever** Fixed

**Bandsaw Blade Speed** N/A

**Bundle Cut?** Yes

## **Product Description**

Dual Column Band Saws
> Wide Flange/Bundle Saws

>> WF1827 Series

The WF1827M band saw is designed to cut structural shapes and bundles efficiently using a fixed 9.2? canted blade. Operated with a touch-screen control mounted in a swing-away console it includes a full-stroking bi-directional main vise. Many options are available including additional top clamps and outboard vise.

## **Standard Features**

Swing-Away Control Console w/7" Touch Screen

24" Roller Discharge Table

Vise - Full Stroking Bi-Directional Main

Adjustable Clamping Force Arm Cant - 9.2° Permanent Carbide Blade Guides

Lead In/Lead Out Roller Guides

Guide Arm - Powered

Variable Blade Speed w/ Readout on Touch Screen

Adjustable Feed Rate Adjustable Cutting Pressure Powered Blade Tension

Coolant System - Flood w/ Wash-Down Hose

**Two-Hand Operation Controls** 

Blade Brush

Broken Blade Function Automatic Blade Idle Blade Change Interlock

Safety Guards

220V/3PH or 440V/3PH Electrical Motor

Requirement - This is Not a Dual Voltage Machine

## **Optional Features**

Top Clamp - Full Capacity Main Vise

Vise - Bi-Directional Outboard

Chip/Swarf Removal System - Chip Conveyor

**Spray Mist Lubrication** 

Pedestal Mounted Control Console

Hydraulic Tank Heater

10' Idle Roller Load Table

Top Clamp - Full Capacity Outboard Vise

Passive "Cut Watcher®" System

Laser Light System

Dual Spray Mist Lubrication - Flood/Mist Selector

Switch

**Roll-Around Control Console** 

Cold Weather Package

5' Discharge Table Extension

**HEMSAW.COM** 

1 (888) 729-7787