



Product Description

Dual Column Band Saws

> Wide Flange/Bundle Saws

>> WF190 Series

The WF190M band saw is designed to cut structural shapes and bundles efficiently using a fixed 9.2° canted blade. Operated with a touch-screen control mounted in a swing-away console it includes a full-stroking bi-directional main vise. Many options are available including additional top clamps and outboard vise.

Technical Specifications

Rectangular Capacity	0-44" W x 0-25" H
Square Capacity	0-25" (Square)
Round Capacity	0-25" (Diameter)
Bar-feed	N/A
Motor	15 HP
Hydraulic Motor	5 HP
Operation Type	Semi-Automatic
Power Source	Hydraulic
Weight	N/A
Blade Type	Bandsaw
Blade Size	29' 0" L x 2" H x .063"
Cantilever	
Bandsaw Blade Speed	N/A
Bundle Cut?	Yes

Standard Features

Swing-Away Console - Semi-Automatic Control
 Arm Cant - 9.2° Permanent
 24" Roller Discharge Table
 Vise - Full Stroking Bi-Directional Main
 Adjustable Clamping Force
 Carbide Blade Guides
 Lead In/Lead Out Roller Guides
 Guide Arm - Powered
 Adjustable Feed Rate
 Adjustable Cutting Pressure
 Variable Blade Speed w/ Readout on Touch Screen
 Powered Blade Tension
 Coolant System - Flood w/ Wash-Down Hose
 Blade Brush
 Two-Hand Operation Controls
 Broken Blade Function
 Automatic Blade Idle
 Blade Change Interlock
 Safety Guards
 220V/3PH or 440V/3PH Electrical Motor
 Requirement - This is Not a Dual Voltage Machine

Optional Features

Top Clamp - Full Capacity Main Vise
 Vise - Bi-Directional Outboard
 Chip/Swarf Removal System - Chip Conveyor
 Laser Light System
 Spray Mist Lubrication
 Pedestal Mounted Control Console
 Hydraulic Tank Heater

Top Clamp - Full Capacity Outboard Vise
 2-5/8" Blade Option - HD Gear Box
 Passive "Cut Watcher®" System
 Shadow Light System
 Cold Weather Package
 Free-Standing Control Console
 10' Idle Roller Load Table

5' Discharge Table Extension
5' Idle Roller Stock Table
10' Powered Roller Stock Table

10' Powered Discharge Table Extension
10' Idle Roller Stock Table

HEMSAW.COM

1 (888) 729-7787