

WF190MRB



Technical Specifications

Rectangular Capacity 0-44" W x 0-25" H

Square Capacity 0-25" (Square)

Round Capacity 0-25" (Diameter)

Bar-feed N/A

Motor 15 HP

Hydraulic Motor 5 HP

Operation Type Semi-Automatic

Power Source Hydraulic

Weight N/A

Blade Type Bandsaw

Blade Size 31' 4" L x 2" H x .063"

Cantilever

Bandsaw Blade Speed N/A

Bundle Cut? Yes

Product Description

Dual Column Band Saws

> Dual Column Double-Miter Saws

The WF190MRB-DC is a powered double-miter band saw operated using a touch screen mounted in a pedestal control console and cuts miter angles 45? in one direction and up to 60? the other direction. Included are vises on both sides of the blade with additional clamping optional.

Standard Features

Pedestal Mounted Control Console w/7" Touch

Screen

Rotary Base Machine

Powered Miter w/ Angle Readout

Arm Cant - 7° Permanent

Vises on Both Sides of the Blade

Adjustable Clamping Force

Adjustable Feed Rate

Adjustable Cutting Pressure

Carbide Blade Guides

Lead In/Lead Out Roller Guides

Guide Arm - Powered

Variable Blade Speed w/ Readout on Touch Screen

Powered Blade Tension

Coolant System - Flood w/ Wash-Down Hose

Blade Brush

Two-Hand Operation Controls

Automatic Blade Idle Broken Blade Function Blade Change Interlock

Safety Guards

220V/3PH or 440V/3PH Electrical Motor

Requirement - This is Not a Dual Voltage Machine

Optional Features

Telescoping Roller Table - Input Side

Top Clamp (Available Input & Output Sides)

Passive "Cut Watcher®" System

Laser Light System
Sproy Mist Lubricat

Spray Mist Lubrication

Hydraulic Tank Heater

Telescoping Roller Table - Output Side

Positioning Vise

Chip/Swarf Removal System - Chip Conveyor

Shadow Light System

Cold Weather Package